

3090-73


Steel wire ropes. Locked conveying wire rope with one layer of Z-wire and type TK cope. Dimensions

12 5100, 12 5200

01.01.75

1.

1+6+12 1+6+12+18.



2.

D	S		S	E0	r	r ₂	100	, (), , / 2 (/ 2)					
	£ S	§						1180 (120)	1270 (130)	1370 (140)	1470 (150)	1570 (160)	1670 (170)
30,5	4,1	19	5	19	19,25	616,59	524,98	724,5 (73950)	785 (80150)	845,5 (86300)	906 (92450)	966,5 (98650)	1020 (104500)
32,0	4,4	19	5	20	19,25	673,90	573,71	792 (80850)	858 (87600)	924 (94300)	989,5 (101000)	1050 (107500)	1120 (114500)
34,0	3,4	37	5	21	19,25	740,18	630,06	870 (88800)	942,5 (96200)	1010 (103500)	1085 (111000)	1155 (118000)	1225 (125500)
35,5	3,6	37	5	22	19,25	800,12	681,03	940,5 (96000)	1015 (104000)	1095 (112000)	1175 (120000)	1250 (128000)	1330 (136000)

1.(, . 2).

.2 3090-80

2.
3.

01.01.91.

1370 / 2 (140 / 2)

34,0 , l,

1180 / 2 (120 / 2):

34,0-1 — — — 1180 3090-73

(
3. , . 1,2).

— 18899.

1.

2.

15.06.73 1484

3.

3090-55

4.

-

18899-73

3

5.

4-93

(4-94)

-

6.

1,2,

1985 .,

1982 . (6-85,

3-90)